





COMBO 5K400 LCD - All Rounder

UNIQUE BENEFITS

- Control panel interface with key pad and leds with 5 heat output levels
- Power board unit
- Hydraulic radiator group
- Inductor transformer cable (3,0 m)
- Foot pedal accessory with cable (2,2 m)

APPLICATIONS

The Combo 5K400 LCD heat inductors are ideal for a wide range of applications such as:

COLLISION

- Heated rear windows/side windows
- Car sunroof glass
- **Moldings**
- Adhesives and stickers without residues paint
- Sealants and/or sound insulation materials
- Tar liner
- Structural glue

INDUCTION:

- Blocked tyres
- Wheel alignement

INCLUDED ACCESSORIES



ART: IND/GLOVE.C **HEATING GLOVE**



ART: IND 5kW/S03 50 INDUCTOR HEAD



ART: IND/GLASS.C **GLASS REMOVER**



ART: DENT-001.C **DENT REMOVAL**

2 MACHINES IN



ART - iT COMBO 5K all rounder

CUSTOMIZATION ON REQUEST

Technical features



400x340x1000h mm



800x800x1280h mm



66 KG



Input power 5 kW - 16 A Electrical connection IEC60309



400V/3PH+T 50 230V/1PH (or 3PH)





Working frequency 15-30 Khz



Duty cycle 30 min* (* ± 5% based on 20°C room temperature @ max power)



■ 8 m Network cable



IP IP 21 Degree of protection



Main circuit breaker



20lt tank - Liquid cooling system



Hydraulic heat exchanger with fan





