



HDi 11K400 KB

UNIQUE BENEFITS

- Adaptive inductance field reading (autotuning)
- Electronic safety protection
- Heating temperature level setting
- User friendly keyboard (color touch control panel 5" upon request)
- Long inductor cable 4.25 m
- **Plug and Play** with art. IND11kW/M inductor head



10+
inductor
heads extra
on request

APPLICATIONS

The HDi 11K400 KB heat inductors are ideal for a wide range of applications such as:

- Bolts/nuts releasing
- Pin or bearing release and replacement
- Heating for straightening
- Pre-heating before welding
- Bending
- Hardening
- Annealing

OPTIONALS



TIMER



HEAT
SENSOR IRT




PEDAL SWITCH



SHS



WIFI



INDUCTOR HEAD
HANDLE



ART - HDi 11K400 KB

CUSTOMIZATION ON REQUEST

Technical features



550x560x1009h mm



800x850x1350h mm



120 KG



Input power 11 kW - 16 A
Electrical connection IEC60309



400V/3PH+T 50



Working frequency 15-30 KHz



8 m Network cable



IP 21 Degree of protection



Main circuit breaker



20lt tank - Liquid cooling system



Hydraulic heat exchanger with fan



ERC UK CA Directives and
Certification