



FULL RANGE | BEST PERFORMANCE | ALL-ROUND

HDi 8K400 TC

UNIQUE BENEFITS

- Adaptive inductance field reading (autotuning)
- User friendly keyboard (color touch control panel 5" upon request)
- Long inductor cable 3.0 m
- Plug and Play with art. IND 5kW/S03 inductor head



heads extra on request



ART - HDi 8K400 TC

CUSTOMIZATION ON REQUEST

APPLICATIONS

The HDi HDi 8K400 TC heat inductors are ideal for a wide range of applications such as:

- Bolts/nuts releasing
- Pin or bearing release and replacement
- Heating for straightening
- Pre-heating before welding
- Bending
- Hardening
- Annealing

OPTIONALS



TIMER

SHS



HEAT SENSOR IRT



WIFI



PEDAL SWITCH



INDUCTOR HEAD **HANDLE**

Technical features



635x525x1080h mm



800x850x1350h mm



59 KG



Input power 8 kW - 16 A Electrical connection IEC60309



230V/400V 3PH+T 50



Working frequency 15-30 Khz



= 6 8 m Network cable



P IP 21 Degree of protection



→ Main circuit breaker



20lt tank - Liquid cooling system



Hydraulic heat exchanger with fan







Directives and Certification