



## iT 5K230 KB

### UNIQUE BENEFITS

- Power level setting (kW)
- Multiple system temperature indicators (°C/°F)
- Keyboard (User friendly LCD panel with 5 heat output levels upon request)
- Long inductor cable (3.0 m)
- **Plug and Play** with art. IND 5kW/S03 inductor head



**10+**  
inductor  
heads extra  
on request



**ART - iT 5K230 KB**

### APPLICATIONS

The iT 5K230 KB heat inductors are ideal for a wide range of applications such as:

- Bolts/nuts releasing
- Pin or bearing release and replacement
- Bending
- Removing suspensions, shock absorbers, exhaust mufflers
- Straightening drive shafts

### OPTIONALS



PEDAL SWITCH



LCD PANEL

### CUSTOMIZATION ON REQUEST

#### Technical features

400x340x1000h mm

800x800x1280h mm

53 KG

Input power 5 kW - 16 A  
Electrical connection IEC60309

230V/3PH+T 50 Hz  
230V/1PH+T 50

Working frequency 15-30 KHz

Duty cycle 30 min\* (\* ± 5% based on 20°C room temperature @ max power)

8 m Network cable

**IP** IP 21 Degree of protection

Main circuit breaker

20lt tank - Liquid cooling system

Hydraulic heat exchanger with fan

Directives and Certification