



iT 6K400 LCD

UNIQUE BENEFITS

- Power level setting (kW)
- Multiple system temperature indicators (°C/°F)
- User friendly LCD panel with 5 heat output levels (Keyboard upon request)
- Long inductor cable (3.0 m)
- **Plug and Play** with art. IND 5kW/S03 inductor head



10+
inductor
heads extra
on request



ART - iT 6K400 LCD

APPLICATIONS

The iT 6K400 LCD heat inductors are ideal for a wide range of applications such as:

- Bolts/nuts releasing
- Pin or bearing release and replacement
- Bending
- Removing suspensions, shock absorbers, exhaust mufflers
- Straightening drive shafts

OPTIONALS



PEDAL SWITCH


CUSTOMIZATION ON REQUEST



Technical features

 400x340x1000h mm


 800x850x1280h mm

 66 KG

 Input power 6 kW - 16 A
Electrical connection IEC60309

 400V/3PH+T 50 

 Working frequency 15-30 KHz


 Duty cycle 30 min* (* ± 5% based on 20°C room temperature @ max power)

 8 m Network cable

IP IP 21 Degree of protection

 Main circuit breaker

 20lt tank - Liquid cooling system

 Hydraulic heat exchanger with fan

   Directives and Certification